

WHAT IS CLAIMED IS:

1/ A receptacle for containing a cosmetic, the receptacle comprising:

- a body; and
- 5 - a neck, comprising:
 - a first portion having a first diameter, and having first fixing means; and
 - a second portion situated between the body of the receptacle and the first portion, said second portion
 - 10 having a second diameter greater than the first diameter, and having second fixing means.

2/ A receptacle according to claim 1, wherein the neck has a shoulder connecting the first portion to the second

15 portion.

3/ A receptacle according to claim 2, wherein the shoulder defines a plane annular surface extending outside the neck, perpendicularly to the axis of the

20 neck.

4/ A receptacle according to claim 1, wherein at least one of the first and second portions includes a thread.

25 5/ A receptacle according to claim 4, wherein the first and second portions have respective threads, these threads enabling screw fastening to be performed by turning in the same direction.

30 6/ A receptacle according to claim 1, wherein at least one of the first and second portions includes at least one snap-fastening shape in relief.

7/ A receptacle according to claim 6, wherein the snap-

35 fastening shape in relief comprises an annular bead.

8/ A receptacle according to claim 1, the receptacle being made of a plastics material.

5 9/ A receptacle according to claim 1, wherein the first portion presents a first inside diameter and the second portion presents a second inside diameter greater than the first inside diameter.

10 10/ A receptacle according to claim 1, wherein the neck has an inside shoulder connecting the first portion and the second portion together.

15 11/ A kit comprising a receptacle as defined in claim 1 together with at least one accessory configured for fixing on the neck.

12/ A kit according to claim 12, wherein the accessory is configured for fixing to the second portion.

20 13/ A kit according to claim 11, wherein the accessory includes a assembly skirt configured for fixing on the second portion, and wherein said assembly skirt has a sealing surface for coming to bear against a shoulder connecting together the first and second portions of the
25 receptacle.

14/ A kit according to claim 13, wherein the sealing surface is defined by an annular bead.

30 15/ A kit according to claim 13, wherein the accessory does not have a sealing lip that comes to bear against the inside of the neck of the receptacle.

35 16/ A kit according to claim 11, wherein the accessory is constituted by an applicator.

17/ A kit according to claim 16, wherein the applicator includes teeth.

18/ A kit according to claim 17, wherein at least one of
5 said teeth includes at least one dispenser orifice.

19/ A kit according to claim 18, wherein said at least
one dispenser orifice is at a distance from the free end
of the corresponding tooth.

10

20/ A kit according to claim 19, wherein said at least
one dispenser orifice is oriented in such a manner as to
limit the risk of substance being dispensed other than
between the teeth.

15

21/ A kit according to claim 16, wherein the applicator
includes at least one row of teeth having end teeth
situated at the ends of the row, said end teeth having no
dispenser orifices that open out other than into a gap
20 between teeth.

22/ A kit according to claim 21, wherein the end teeth
have no dispenser orifices.

23/ A kit according to claim 21, wherein at least one of
25 the teeth of the row situated between the end teeth has
two dispenser orifices opening out sideways on either
side of the tooth in a direction parallel to the row.

24/ A kit according to claim 23, wherein all of the teeth
30 situated between the end teeth have at least one
dispenser orifice.

25/ A kit according to claim 18, wherein at least one of
35 the teeth is provided with a groove extending from its
free end to a dispenser orifice.

26/ A kit according to claim 17, wherein the applicator has at least six teeth each provided with at least one dispenser orifice.

5 27/ A kit according to claim 17, wherein all of the teeth of the applicator are of the same length.

28/ A kit according to claim 16, wherein the applicator is made by molding.

10

29/ A kit according to claim 11, at least one of the first and second portions including a thread; the kit including at least one accessory configured for screwing onto said thread.

15

30/ A kit according to claim 11, at least one of the first and second portions including at least one snap-fastening shape in relief, the kit including at least one accessory provided with at least one complementary snap-fastening shape in relief suitable for co-operating with the snap-fastening shape in relief of the receptacle.

20

31/ A kit according to claim 11, including at least two accessories of different kinds.

25

32/ A kit according to claim 31, wherein the two accessories are designed for fixing respectively to the first portion and to the second portion.

30 33/ A kit according to claim 31, wherein one of the accessories is constituted by a cap and the other accessory by an applicator.

35 34/ A kit according to claim 31, including an accessory configured for fixing on the first portion.

35/ A kit according to claim 34, wherein the accessory configured for fixing on the first portion is selected from a cap, an endpiece, and a receptacle.

5 36/ A kit according to claim 11, wherein the receptacle is filled with a cosmetic.

37/ A kit according to claim 36, wherein the cosmetic is a substance for coloring the hair.

10

38/ An applicator configured for fixing on the neck of a receptacle, the applicator including a assembly skirt configured for fixing on the receptacle, provided with an annular bead made on the inside surface of the skirt, at
15 a distance from the free end thereof.

39/ An applicator according to claim 38, for screw fastening on the neck of a receptacle.

20 40/ A receptacle comprising:

- a body; and

- a neck, comprising:

- a first portion having a first inside diameter, and having first fixing means; and

25 - a second portion situated between the body of the receptacle and the first portion, said second portion having a second inside diameter greater than the first inside diameter, and having second fixing means.

30 41/ A receptacle comprising:

- a body; and

- a neck, comprising:

- a first portion having a first diameter, and having first fixing means;

35 - a second portion situated between the body of the receptacle and the first portion, said second portion

having a second diameter greater than the first diameter,
and having second fixing means; and

- an inside shoulder connecting the first
portion to the second portion.

5

42/ A receptacle comprising:

- a body; and

- a neck, comprising:

10 - a first portion having a first diameter, and
having a first thread; and

- a second portion situated between the body of
the receptacle and the first portion, said second portion
having a second diameter greater than the first diameter,
and having a second thread, the first and second threads
15 enabling screw fastening to be performed by turning in the
same direction.

43/ A receptacle for containing a cosmetic, the
receptacle comprising:

20 - a body; and

- a neck, comprising:

- a first portion having a first diameter, and
having at least one of a first thread and a first snap-
fastening shape in relief; and

25 - a second portion situated between the body of
the receptacle and the first portion, said second portion
having a second diameter greater than the first diameter,
and having at least one of a second thread and a second
snap-fastening shape in relief.

30

44/ A kit comprising:

- a receptacle comprising:

- a body; and

- a neck, comprising:

35 - a first portion having a first diameter
and including first fixing means; and

- a second portion situated between the body of the receptacle and the first portion, said second portion having a second diameter greater than the first diameter, and having second fixing means; and

5 - at least two accessories of different kinds.

45/ A kit according to claim 44, wherein the at least two accessories are selected from an applicator, an endpiece a cap, and a receptacle.

10

46/ A kit comprising:

- a receptacle comprising:

- a body; and

- a neck, comprising:

15 - a first portion having a first diameter and including first fixing means; and

- a second portion situated between the body of the receptacle and the first portion, said second portion having a second diameter greater than the first diameter, and having second fixing means; and

20

- at least two accessories for fixing to the first and second portions respectively.

47/ A kit according to claim 46, wherein the accessories are selected from an applicator, an endpiece, a cap, and a receptacle.

25